



*schilling*  
Marking Systems GmbH

# User Guide

## Memory Card for Palm

05.11.2007

k:\bedienungsanltg\nadelpräger\mega-marker\speicherkarte\memory-card for palm\_gb.doc



Schilling Marking Systems GmbH  
In Grubenäcker 1 DE-78532 Tuttlingen



+49 (0)7461 9472-0



+49 (0)7461 9472-20



[www.schilling-marking.de](http://www.schilling-marking.de)  
[info@schilling-marking.de](mailto:info@schilling-marking.de)




# Content:

<b>CONTENT OF THE MEMORY CARD.....</b>	<b>2</b>
<b>INSTALLATION OF THE SOFTWARE AFTER DISCHARGING THE PALM (BATTERY EMPTY).....</b>	<b>2</b>
<b>SAVING THE JOBS ONTO THE MEMORY CARD .....</b>	<b>4</b>
<b>BACKING UP THE JOBS FROM THE MEMORY CARD .....</b>	<b>5</b>



## Content of the Memory Card

The following directories and files are already in the palm at the delivery:



## Installation of the Software after discharging the Palm (battery empty)

1. Charge the Palm with the original AC adapter (about 8 hours).
2. Switch on the Palm and follow the starting procedure on the screen.
3. Put the memory card into the Palm (remove dummy first), until it clicks into place.

4. Click on the clock in the top left corner.



5. In the menu, click on Copy.



6. ! Attention ! „Copy to:“ has to be set on >>Handheld<< !  
The **name of the card** will be at „From:“  
(The name of the card may be different from the one in the picture)



7. Choose every single file separately and confirm with >>copy<<.



After having copied all three files, end with >>Finish<< .

Now, the icons „Fly“ and „ConMgr“ will be back on the palm screen.

8. Execute „Reset“. Use the palm pen to press the reset button on the rear side of the palm.



Sony Clie



Tungsten W

After the screen is “rebuilt”, the Fly-Software will work again.

# Saving the Jobs onto the Memory Card

**!! Attention !!**

**The existing file on the memory card will be replaced**

1. Put the memory card into the Palm (remove Dummy first), until it clicks into place.

2. Click on the clock in the top left corner.



3. In the menu, click on Copy.



4. ! Attention ! „Copy to:“ has to be set on >>Card<< !  
(The name of the card may be different from the one in the picture)  
“Handheld” will be at „From:“



5. Choose the file „Fly“ and confirm with >>copy<< .



After having copied the file completely, end with >>Finish<<.

The actual file „Fly“ together with all the jobs is now saved on the memory card.

# Backing up the Jobs from the Memory Card

**!! Attention !!**

**The existing jobs on the palm will be replaced**

1. Put the memory card into the Palm (remove Dummy first), until it clicks into place.

2. Click on the clock in the top left corner.



3. In the menu, click on Copy.



4. ! Attention ! „Copy to:“ has to be set on >>Handheld<< !  
The card name will be at „From:“  
(The name of the card may be different from the one in the picture)



5. Choose the file „Fly“ and confirm with >>copy<< .



After having copied the file completely, end with >>Finish<<.

The file „Fly“ together with all the jobs is now backed up on the Palm.

6. Execute „Reset“. Use the palm pen to press the reset button on the rear side of the palm.



Sony Clie



Tungsten W

After the screen is “rebuilt”, the Fly-Software with the backed up jobs will work again.