


Mega - Marker™

A class better!



- * *The universal, free programmable marking system with future orientated control system.*
- * *Permanent direct part marking in seconds*
- * *Easy operation by PDA and Fly software.*
- * *New graphic user interface without PC*
- * *All-In-One device, sturdy, reliable, save space, professional.*
- * *Convenient creation of jobs on desk or in workshop. Perfect results.*
- * *Software Fly will not leave any wishes open.*



Marking area x / y	100 x 100 mm
Height adjustment	298 mm
Marking speed	1 mm/s to 80 mm/s
Traverse speed	max. 80 mm/s
Marking head orientation	No limits
Marking resolution	0,05 mm, both X/Y axes
Character height	off 0,1 mm free editable
Stylus frequency	0 - 150 Hz
Impact force	adjustable
Height compens. of needle	approx. 10 mm
Air requirements	300 l/min
Working pressure	max. 7 bar
	Dimensions (LxWxH;mm)
Marking Head	250x270x240
Column and base	370x400x760
	approx. Weight in kg
Marking Head	9,4
Column and base	18,6
Supply	90-265VAC 50/60 Hz
Memory	1 MB Flash / 1 MB RAM
Font	DIN 1451m
Formats	Text linear, angle- and circular, date, counter with Pre- & Suffix function, logos on request
Brand	Mega-Marker is a registered trademark



Specifications PDA Palm Tungsten W:

Manufacturer	: Palm	Expansion slot	: MMC/SD
Memory RAM	: 16 MB	Battery type	: Rechargeable lithium-ion
Operating system	: PalmOS® 4.1.1	Desktop applic.:	Mobile phone, Organizer, Web browsing & eMail, hand writing recognition
Display type	: 320x320 TFT color display and LED-backlight illumination	Size	: 137 x 78 x 17 mm
Interfaces	: USB, Infrared, Bluetooth, GSM	Weight	: approx. 184 g
Audio/Features	: MP3-Player headset universal, 2.5mm mini stereo jack, Microphone		


Needle Set for better results

Art.-Nr.: 66.64SET.3




- light exchange needle with 60° / 90° / 118°
- normal piston and short piston, with appropriate spring
- o-rings, washers and allen-key


Needle assemblies compl.



Heavy
Needle assembly ø6mm
 for deep markings
 Standard angle of the tip: 60°
 other angles: 90° / 118°
 Art.-Nr.: 66.62150.6S




Light
Needle assembly ø3mm
 for normal markings
 Standard angle of the tip: 60°
 other angles: 90° / 118°
 Art.-Nr.: 66.62032.3S




Light, soft
Needle assembly ø3mm
 for fine markings
 Standard angle of the tip: 60°
 other angles: 90° / 118°
 Art.-Nr.: 66.62132.3S

Tungsten carbide exchange needles



Heavy
Exchange needle ø6mm
 available angles:
 60° - Art.-Nr.: 66.64060.6S
 90° - Art.-Nr.: 66.64090.6S
 118° - Art.-Nr.: 66.64118.6S



Light
Exchange needle ø3mm
 available angles:
 60° - Art.-Nr.: 66.64060.3S
 90° - Art.-Nr.: 66.64090.3S
 118° - Art.-Nr.: 66.64118.3S

Needle extension



to adjust the spacer distance from the needle tip and the marking head. Spacer extension: 70mm
 Art.-Nr.: 66.60007.3