

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Electrolyte AE 4

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use Electrolytic marking technology

1.3 Details of the supplier of the safety data sheet

Company name: Schilling Marking Systems GmbH

Street/POB-No.: In Grubenäcker 1

Postal Code, city: 78532 Tuttlingen

Germany

WWW: www.schilling-marking.de

E-mail: info@schilling-marking.de

Telephone: +49 (0)7461 9472-17

Telefax: +49 (0)7461 9472-29

Dept. responsible for information:

Herr Andreas Schilling,

Telephone: +49 (0)7461 9472-15, Email: info@schilling-marking.de

1.4 Emergency telephone number

Beratungsstelle für Vergiftungserscheinungen, Berlin,

Telephone: +49 (0)30 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Sens.; R43 May cause sensitization by skin contact.

2.2 Label elements

Labelling (67/548/EEC or 1999/45/EC)



Xi

irritant

R phrase(s): R 43 May cause sensitization by skin contact.

S phrase(s): S 2 Keep out of the reach of children.

S 24 Avoid contact with skin.

S 37 Wear suitable gloves.

Text for labelling Contains Mixture of 5-chlorine-2-methyl-2H-isothiazol-3-on and 2-methylen-2H-isothiazol-3-on (3:1).

2.3 Other hazards

Electrolytic vapours may form during the electrochemical process.

Electrolyte AE 4

Material number 22.004

Version 3 / Page 2 of 7

SECTION 3: Composition/ information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterization (preparation):

mixture of water/mineral salt and complexing agent

Hazardous ingredients:

Ingredient	Chemical name	Content	Classification
EINECS - CAS 55965- 84-9	Mixture of 5-Chloro-2-methyl-2H- isothiazolin-3-one and 2-methyl-2H-isothiazol-3- one (3:1) [EC-No. 247-500-7 + 220-239-6]	0,0015-0,06 %	EU: C; R34. Sens.; R43. N; R50-53. T; R23/24/25. CLP: Acute Tox. 3; H301. Acute Tox. 3; H311. Acute Tox. 3; H331. Skin Corr. 1B; H314. Skin Sens. 1; H317. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.

SECTION 4: First aid measures**4.1 Description of first aid measures**

After inhalation: Provide fresh air. In case of respiratory difficulties seek medical attention.

In case of skin contact: Change contaminated clothing.
After contact with skin, wash immediately with plenty of water.
In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water.
If you feel unwell, seek medical advice.**4.2 Most important symptoms and effects, both acute and delayed**

No data available

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media:

Product is non-combustible. Extinguishing materials should therefore be selected according to surroundings.

5.2 Special hazards arising from the substance or mixtureIn the event of a fire, the following may be produced when the water evaporates:
Chlorine decomposition products (in traces).**5.3 Advice for firefighters**

Special protective equipment for firefighters:

Wear self-contained breathing apparatus.

Additional information: Hazchem-Code: -

Do not allow fire water to penetrate into surface or ground water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with the substance. Provide adequate ventilation.

6.2 Environmental precautions

Do not allow to penetrate into soil, waterbodies or drains.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent materials such as sand, siliceous earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance. Final cleaning.

6.4 Reference to other sections

Refer additionally to chapter 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling Provide adequate ventilation, and local exhaust as needed.
Avoid contact with the substance. Do not breathe vapour/aerosol.
Do not mix with other chemicals.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Keep container tightly closed.

Storage class: 12= Non-combustible liquids

7.3 Specific end use(s)

Electrolytic marking technology

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information: Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Occupational exposure controls

Respiratory protection: If vapours form, use respiratory protection.
Use filter type A-P3 according to EN 14387.

Hand protection: Protective gloves according to EN 374.
Glove material: Butyl caoutchouc (butyl rubber)-Breakthrough time: >480 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to EN 166.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures:
Change contaminated clothing.
Wash hands before breaks and after work.

Electrolyte AE 4

Material number 22.004

Version 3 / Page 4 of 7

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic
Flash point / flash point range:	not combustible
Density:	at 20 °C: 1,03 g/mL
pH value:	6,5-7,5
Water solubility:	at 20 °C: fully miscible

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

see 10.3

10.2 Chemical stability

Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

Do not mix with other chemicals.

10.5 Incompatible materials

strong acids and alkalis

10.6 Hazardous decomposition products

In the event of a fire, the following may be produced when the water evaporates:
Chlorine decomposition products (in traces).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects

Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Lack of data.
Eye damage / irritation: Based on available data, the classification criteria are not met.
May cause irritations.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Skin Sens. 1; H317.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

General remarks

May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about Mixture of 5-chlorine-2-methyl-2H-isothiazol-3-on and 2-methylen-2H-isothiazol-3-on (3:1) (Biocide):
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Algae toxicity:
EC50 Pseudokirchneriella subcapitata: 0,018 mg/L/72h.
EC50 Selenastrum capricornutum: 0,025 mg/L/96h.
Bacterial toxicity:
EC50 Pseudomonas putida: 5,7 mg/L/16h.
Daphnia toxicity:
EC50 Daphnia magna: 0,12 mg/L/48 h.
Fish toxicity:
LC50 trout: 0,19 - 0,28 mg/L/96 h.

Water Hazard Class: 1 = slightly hazardous to water

12.2. Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number 11 01 98* = Wastes from chemical surface treatment and coating of metals and other materials (eg. galvanic processes, zinc coating processes, pickling processes, etching, phosphatising, alkaline degreasing, anodising)
* = Evidence for disposal must be provided.

Recommendation: Special waste. Dispose of waste according to applicable legislation.

Contaminated packaging

Waste key number 15 01 02 = Plastic packaging

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

not applicable

14.2 UN proper shipping name

ADR/RID, IMDG, IATA: Not restricted

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Marine pollutant - IMDG: No

14.6 Special precautions for user

No dangerous good in sense of these transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: -

Electrolyte AE 4

Material number 22.004

Version 3 / Page 7 of 7

National regulations - Germany

Storage class: 12= Non-combustible liquids
Water Hazard Class: 1 = slightly hazardous to water

Informations on working limitations:
Observe employment restrictions concerning young persons.

National regulations - EC member states

Volatile organic compounds (VOC):
approx. 0,4 % by weight

National regulations - USA

Hazard rating systems



NFPA Hazard Rating:
Health: 1 (Slight)
Fire: 0 (Minimal)
Reactivity: 0 (Minimal)

HMIS Version III Rating:
Health: 1 (Slight)
Flammability: 0 (Minimal)
Physical Hazard: 0 (Minimal)
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
	X

15.2 Chemical Safety Assessment

No data available

SECTION 16: Other information

Further remarks

Wording of the R-phrases under paragraph 2 and 3:

R 23/24/25 = Toxic by inhalation, in contact with skin and if swallowed.

R 34 = Causes burns.

R 43 = May cause sensitization by skin contact.

R 50/53 = Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Reason of change: General revision

Group that issues data sheet

Contact person: see chapter 1, department responsible for information.

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.